

DRB SAFETY BARRIERS

UNIT 27, CHEMICAL LANE, LONGBRIDGE HAYES INDUSTRIAL ESTATE,
LONGBRIDGE HAYES, STOKE-ON-TRENT, STAFFORDSHIRE, ST6 4PB

TELEPHONE: (01782) 836080 FACSIMILE: (01782) 833030

EMAIL: SALES@DRBSAFETYBARRIERS.CO.UK

WEB SITE: WWW.DRBSAFETYBARRIERS.CO.UK

TECHNICAL DATA

ALL DIMENSIONS IN MM

	MAX PALLET HEIGHT	MAX PALLET DEPTH	MAX PALLET WIDTH	MIN HEADROOM REQUIRED
MODEL ATOM 1500	1500	1450	300mm less than the outer width	2100
MODEL 12	1650	1450	300mm less than the outer width	2100
MODEL 30	2050	1400	300mm less than the outer width	3230
MODEL 30M	2050	1400-2000	300mm less than the outer width	3230
MODEL LC/HP	1800-2400	1450	300mm less than the outer width	300mm higher than the max pallet height

To calculate the width of the pallet gate required add 300mm to the maximum pallet width to be used.

NOTE: It is always advisable to add on at least 100mm to the maximum pallet width.

These are our standard range of pallet gates. If these do not meet your requirements, please refer to our contacts page where we will be pleased to help you.

For more specific data please contact us.